



**Magnesium alloy specification**

Components	Impurities	Percentage (%)
Zinc		2.5 - 3.5
Manganese		0.01 - 0.05
Magnesium		Remainder
	Silicon	0.30 max
	Aluminium	0.25 max
	Copper	0.08 max
	Lead	0.030 max
	Tin	0.010 max
	Ferrous	0.005 max
	Nickel	0.003 max

Electrical capacity: 1230 Ahr / Kg nominal  
Solution potential: -1500 mV vs. Cu/CuSO4 reference cell nominal (in seawater)

Note: All dimensions and weights are nominal. Dimensions in mm  
 All data is subject to change without prior notice  
 Anode can also be provided backside coated

Nett Weight: 2.0 Kg  
 Gross Weight: 2.6 Kg

Date:			<b>Cathodic Protection Division</b> Rietdekkerstraat 16 P.O. Box 4222 2980 GE Ridderkerk Netherlands Tel: +31 (0)180 48 28 28 E-mail: sales@mme.nl www.mme-group.com	Projection: 
	Order number: <b>Magnesium Alloy Hull Anode MME 20M</b>			Scale: 1:5
Description:	Drawn: PdG	Date: 22-02-16	Project:	Sheet 1/1
	Checked: JdR	Date: 22-02-16	Dwg: MME 20M	
Rev.	Approved: PM	Date: 22-02-16	Copyright MME. No part of this drawing may be copied, disclosed, or made public, in any form, without prior written consent of Materiaal Metingen Europe.	

MME 8Z