



Magnesium alloy specification

Components	Impurities	Percentage (%)
Zinc		2.5 - 3.5
Manganese		0.01 - 0.05
Magnesium		Remainder
	Silicon	0.30 max
	Aluminium	0.25 max
	Copper	0.08 max
	Lead	0.030 max
	Tin	0.010 max
	Ferrous	0.005 max
	Nickel	0.003 max

Electrical capacity: 1230 AHr / Kg nominal
Solution potential: -1500 mV vs. Cu/CuSO4 reference cell nominal (in seawater)

Note: All dimensions and weights are nominal. Dimensions in mm
 All data is subject to change without prior notice
 Anode is fitted with galvanised insert
 Anode can also be provided backside coated

Nett Weight: 0.24 Kg
 Gross Weight: 0.34 Kg

Date:			Cathodic Protection Division Rietdekkerstraat 16 P.O. Box 4222 2980 GE Ridderkerk Netherlands Tel: +31 (0)180 48 28 28 E-mail: sales@mme.nl www.mme-group.com	Projection: 
	Order number:		Magnesium Alloy Hull Anode MME 4M	
Description:	Drawn: PdG	Date: 22-02-16	Project:	Sheet 1/1
	Checked: JdR	Date: 22-02-16	Dwg: MME 4M	
Rev.	Approved: PJM	Date: 22-02-16	Copyright MME. No part of this drawing may be copied, disclosed, or made public, in any form, without prior written consent of Materiaal Metingen Europe.	

A

B

C

MME 12
 A4