



Zinc alloy specifications acc. US Mil. Spec-A-18001K

Components	Impurities	Percentage (%)
Cadmium		0.025 - 0.07
Aluminium		0.10 - 0.5
Zinc		Remainder
	Copper	0.005 max
	Iron	0.005 max
	Lead	0.006 max
	Others total	0.10 max

Electrochemical capacity: 780 AHr/Kg nominal  
Solution potential: -1050mV vs. Ag/AgCl reference cell nominal (in seawater)

Other specifications are available on request.

Note: All dimensions and weights are nominal. Dimensions in mm  
 All data is subject to change without prior notice  
 Tank anodes available with Z-cranked or straight insert (shown)  
 Other insert arrangements on request  
 Anode can also be provided backside coated

Nett Weight: 8.9 Kg  
 Gross Weight: 9.4 Kg

Date:			<b>Cathodic Protection Division</b> Rietdekkerstraat 16 P.O. Box 4222 2980 GE Ridderkerk Netherlands Tel: +31 (0)180 48 28 28 E-mail: sales@mme.nl www.mme-group.com	Projection: 
	Order number:			Scale: 1:5
Description:	<b>Zinc Alloy Tank Anode</b> <b>MME 89ZT Straight</b>			
	Drawn: PdG	Date: 31-07-13	Project:	
Rev.	Checked: JdR	Date: 31-07-13	Dwg: MME 89ZT Straight	Sheet 1/1
	Approved: PM	Date: 31-07-13	Copyright MME. No part of this drawing may be copied, disclosed, or made public, in any form, without prior written consent of Materiaal Metingen Europe.	