

**Description:** HEMPEL'S WAX 69033 is a liquid wax for UV protection and a high gloss durable finish.  
**Recommended use:** For use on gelcoat, painted and varnished surfaces after polishing with HEMPEL'S CUSTOM MARINE POLISH 67444, producing a dirt-repellent, easy to clean surface.

Suitable for both manual and machine use.

**Availability:** Part of European Yacht assortment. Local availability subject to confirmation.

### PHYSICAL CONSTANTS:

Shade nos/Colours: 09990/ Off-white.  
Flash point: 80 °C [176 °F]  
Specific gravity: 1 kg/litre [8 lbs/US gallon]  
pH: 8  
VOC content: 241 g/l [2 lbs/US gallon]  
*The physical constants stated are nominal data according to the HEMPEL Group's approved formulas.*

### APPLICATION DETAILS:

**Safety:** Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult HEMPEL Safety Data Sheets and follow all local or national safety regulations.

**SURFACE PREPARATION:** Clean and degrease the surface with HEMPEL'S PRE-CLEAN 67062 or HEMPEL'S BOAT SHAMPOO 67284 to remove dirt and other contaminants, rinse with fresh water. Allow the surface to dry  
**Surfaces in good condition:** Polishing with: HEMPEL'S CUSTOM MARINE POLISH 67444. Apply: HEMPEL'S WAX 69033.  
**Deteriorated surfaces:** Use: HEMPEL'S RUBBING LIQUID 69021 to restore and renew gloss and colour of gelcoat and painted surfaces followed by: HEMPEL'S CUSTOM MARINE POLISH 67444. Apply: HEMPEL'S WAX 69033.

**PRODUCT APPLICATION:** Shake well before use. Apply the product in a thin layer with clean, soft rags. Treat only small areas at a time. Allow the surface to dry. Polish using a clean, soft cloth or a polishing machine to obtain a more effective performance. Change to clean cloths frequently. Use a new, clean polishing pad when using the polishing machine. To maintain the high gloss performance, apply extra layers when first signs of gloss decrease are observed. Allow freshly painted surfaces to dry/cure for at least 90 days before applying the product. Later if repainting is required, it is very important to remove all traces of wax by using: HEMPEL'S PRE-CLEAN 67602. Rinse the surface with fresh water.

**APPLICATION CONDITIONS :** Do not expose to frost. Do not apply in direct sunlight. The surface temperature should be above: 5°C/41°F.

**SUBSEQUENT COAT:** None.  
To maintain the high gloss performance, apply extra layers when first signs of gloss decrease are observed.

### REMARKS:

Note: **HEMPEL'S WAX 69033**

ISSUED BY: HEMPEL A/S

6903309990

This Product Data Sheet supersedes those previously issued.

For explanations, definitions and scope, see "Explanatory Notes" available on [www.hempel.com](http://www.hempel.com). Data, specifications, directions and recommendations given in this data sheet represent only test results or experience obtained under controlled or specially defined circumstances. Their accuracy, completeness or appropriateness under the actual conditions of any intended use of the Products herein must be determined exclusively by the Buyer and/or User.

The Products are supplied and all technical assistance is given subject to HEMPEL's GENERAL CONDITIONS OF SALES, DELIVERY AND SERVICE, unless otherwise expressly agreed in writing. The Manufacturer and Seller disclaim, and Buyer and/or User waive all claims involving, any liability, including but not limited to negligence, except as expressed in said GENERAL CONDITIONS for all results, injury or direct or consequential losses or damages arising from the use of the Products as recommended above, on the overleaf or otherwise. Product data are subject to change without notice and become void five years from the date of issue.