

Product Data

Hempel's Paint Stripper 69560



Description:	Hempel's Paint Stripper 69560 is a highly effective, solvent based paint remover which can be used on most painted or varnished surfaces.
Availability:	Part of European Yacht assortment. Local availability subject to confirmation.
PHYSICAL CONSTANTS:	
Shade nos/Colours:	00000 / Transparent
Flash point:	101 °C [213.8 °F]
Specific gravity:	1 kg/litre [8.4 lbs/US gallon]
VOC content:	306 g/l [2.6 lbs/US gallon]
Shelf life:	5 years (from date on lid)
	<i>The physical constants stated are nominal data according to the HEMPEL Group's approved formulas.</i>
APPLICATION DETAILS:	
Application method:	Brush / Roller
Safety:	Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult HEMPEL Safety Data Sheets and follow all local or national safety regulations.

Product Data

Hempel's Paint Stripper 69560



SURFACE PREPARATION:	Preparation: It is recommended a small test patch be performed prior to application and the duration of treatment required is noted. Do not apply in direct sunlight.
PRODUCT APPLICATION:	Method: Apply the product liberally with brush or roller to a dry surface. Do not treat too large an area in one step. Cover the treated area with aluminium foil to prevent excessive evaporation of the active solvents. Leave to work for 30-45 minutes until the paint coat dissolves or lifts. Shortest duration for antifouling, alkyd paints and varnishes, longest for silicone and epoxy. Use with caution on glass fibre and plastics (may harm thermoplasts). Scrape off old paint and clean with hot water and a boat shampoo. Old and thick coats may need a repeat treatment.
APPLICATION CONDITIONS :	Application temperature: 10°C/50°F Do not use hot air pistols. Do not apply in strong sunshine, on hot surfaces or under humid conditions. Keep away from flames and hot surfaces.
RECOMMENDED DETERGENT :	HEMPEL'S BOAT SHAMPOO 67284
REMARKS:	
Storage Conditions:	Exposure to air and temperature variances should be avoided. Avoid direct sunlight. Keep containers tightly sealed. Store at temperatures: 5°C/41°F - 35°C/95°F
Overcoating:	If the maximum overcoating interval is exceeded, clean with fresh water and allow to dry. Light abrade and remove all dust prior to repainting. If surface has been contaminated by oils and pollutants, thoroughly remove with suitable detergent, rinse with fresh water and allow to dry. Light abrade and remove all dust prior to repainting.
Note:	Hempel's Paint Stripper 69560
ISSUED BY:	HEMPEL A/S 6956000000

This Product Data Sheet supersedes those previously issued.
For explanations, definitions and scope, see "Explanatory Notes" available on www.hempel.com. Data, specifications, directions and recommendations given in this data sheet represent only test results or experience obtained under controlled or specially defined circumstances. Their accuracy, completeness or appropriateness under the actual conditions of any intended use of the Products herein must be determined exclusively by the Buyer and/or User.
The Products are supplied and all technical assistance is given subject to HEMPEL's GENERAL CONDITIONS OF SALES, DELIVERY AND SERVICE, unless otherwise expressly agreed in writing. The Manufacturer and Seller disclaim, and Buyer and/or User waive all claims involving, any liability, including but not limited to negligence, except as expressed in said GENERAL CONDITIONS for all results, injury or direct or consequential losses or damages arising from the use of the Products as recommended above, on the overleaf or otherwise. Product data are subject to change without notice and become void five years from the date of issue.